

#### **KIT CONSISTS OF:**

- PC75-40R, cutting tool
- Hand pump, with swivel coupling
- 2 m hose with quick couplings
- Couplings for convinence
- Carrying case

# FEATURES OF THE PC75-40R CUTTING TOOL

- Quick and easy to use
- 40 mm opening
- 76 kN max cutting force
- Spring return
- Working pressure 80 MPa
- Works in any position, horizontal or vertical
- Cutting head rotates freely 355°
- Swivel coupling for greater flexiblity



# Hydraulic cutting tool kit

# EHR102A - PC75-40R

The PC75-40R provides a quick, simple solution for hand operating cutting for rescue, police and even industrial applications

#### Information



The hydraulic cutting tool PC75 is a hand operated cutting tool with spring return for cutting pedals in crashed vehicles, for cutting rebar, padlocks, aircraft, train seats and even common tool for cutting steel pipes etc.

# Functionality



The cutting performance of the hydraulic cutting tool PC75 is to cut thru 11SMnPb30+C steel with hardness of 170 HB and a diameter of 18 mm.

# Usability



Fields of use where the PC75 is aplicable may include:


- Rescue services
- Civil defence
- Emergency aid operations
- Scraping and demolition
- Industrial applications



## PC75-40R - PERFORMANCE

Product	Capacity			Max worki	ng pressure	Max opening		Stroke volume		Connection	Weight		
Product	kN	٧	ton	MPa	psi	mm	inch	cm <sup>3</sup>	in <sup>3</sup>	Connection	kg	Ibs	
PC75-40	)R 76	3	7.7	80	11603	40	1.6	38,5	2.3	Swivel coupling	3,5	7.7	







The cutting head rotates freely through 355° PC75-40R. The swivel coupling is capable of rotating 360° even under pressure which guarantees highest possible flexibility when handling the tool.

## PC75-40R - MEASUREMENTS

	Product	A		В		C		D		E		F		G		Н	
		mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
Ì	PC75-40R	313	12.3	42	1.7	77	3.0	44	1.7	40	1.6	45	1.8	53	2.1	33	1.3





#### **PUMP**

## Hand pump - PHS80-300W



Working pressure: 80 MPa, 800 bar, 11600 psi

Effective oil volume: 300 cm3, 18.3 in3

Capacity high pressure: 1 cm<sup>3</sup>/stroke, 0.1 in<sup>3</sup>/stroke Capacity low pressure: 20 cm<sup>3</sup>/stroke, 1.2 in<sup>3</sup>/stroke

Pump force: 400 N

Weight: 4,8 kg, 10.6 lbs

In EHR102A, equipped with swivel ASE10 and female quick coupling AQI8-LD  $\,$ 

## ORDERING INFORMATION

Designation	EHR102A - complete	tool kit								
Part number	51150									
Designation	PC75-40R - Cutting tool	PHS80-3	00W - Hand pump	Swivel coupling ASE10	Quick coupling female AQI8-LD	Quick coupling male AQU8-D				
Part number	38746	44881		37588	45950	45953				

#### REHOBOT Hydraulics AB

Postal address: P.O. Box 1107 631 80 Eskilstuna, Sweden T: +46 (0)16-16 82 00 | F: +46 (0)16-13 93 16 E: info@rehobot.se | www.rehobot.se

#### REHOBOT Ltd.

Unit 6, Stechford Trading Estate, Lyndon Road, Stechford Birmingham B33 8BU, UK
T: +44 121 789 77 07 |F: +44 121 789 68 66
E: info@rehobot.co.uk|www.rehobot.co.uk

REHOBOT Inc. Unit #1 3980 W. Albany St. McHenry II 600 50, USA T: +1 815 385 77 77 F: +1 815 385 77 76 E: info@rehobot.us|www.rehobot.us