

FOMTEC® Enviro Class A Super

Foam concentrate

fomtec
Fire Fighting Foams & Equipment



Fomtec® Enviro Class A Super

FOMTEC Enviro Class A Super

Fomtec Enviro Class A Super is a novel blend of high activity hydrocarbon surfactants, selected for their environmental profile, solvents and stabilizers, for use on class A fuel fires and smaller class B fires. Enviro Class A Super does not contain any fluorinated surfactants or polymers (PFAS) or other organohalogens. Enviro Class A Super does not contain any hazardous substances and does not require any special labelling when transported.

- 100% biodegradable
- Usage 0.1-1% with excellent wetting properties
- Readily mixable, easy to use in field



APPLICATION

Enviro Class A Super provides excellent extinguishments of class A fires by providing deep penetration of the water into the burning material. At low concentrations it is also highly effective as a wetting agent. Enviro Class A Super is also effective on smaller Class B fires. Enviro Class A Super can be used with both aspirating and non-aspirating discharge devices. It is compatible with all dry chemical powders.

Enviro Class A Super can be used in:

- Fire extinguishers
- Foam systems
- CAFS systems

FIRE PERFORMANCE & FOAMING

Enviro Class A Super has been designed to be applied as a Wetting Agent as well as a Class A fire extinguishing agent and can be effective if proportioned from 0,1% to 1,0% according to requirements. The foaming properties are depending on equipment used and other variables such as water and ambient temperatures. Average expansion 10:1, average ¼ drainage time 11:30 minutes using UNI 86 test nozzle.

COMPATIBILITY

Contact the Fomtec sales team with questions. For material compatibility please refer to Fomtec Technical Advices FTA 20 addressing the topic.

ENVIRONMENTAL

Enviro Class A Super is non-hazardous, biodegradable substance formulated using raw materials specially selected for their fire performance and their environmental profile. The product is totally free from fluorinated surfactants and polymers and other organohalogens, and therefore it does not contain any PFAS. The handling of spills of concentrate or foam solutions should however be undertaken according to local regulations. Normally sewage systems can dispose foam solution based on this type of foam concentrate, but local sewage operators should be consulted. Full details will be found in the Material Safety Datasheet (MSDS). For more detailed information please consult Fomtec Technical Advices FTA 40.

STORAGE / SHELF LIFE

Stored in original unbroken packaging the product will have a long shelf life. Shelf life in excess of 10 years will be found in temperate climates. As with all foams, shelf life will be dependent on storage temperatures and conditions. For storage recommendations and material compatibility please refer to our Fomtec Technical Advices FTA 10 addressing the topic.

TYPICAL DATA

Appearance	Clear yellowish liquid
Specific gravity at 20°C	1,03 +/- 0.01 g/ml
Viscosity at 20°C	≤ 30 mPas
pH	6,5 – 8,5
Freezing point	-5°C
Recommended storage temperature	-5 - 55°C
Surface tension	≤ 25,0 mN/m

INSPECTION/TESTING/ MAINTENANCE

The foam concentrate should be tested annually. The testing should be made by a suitable laboratory for analysis of foam concentrates and should measure: pH, specific gravity, expansion, drainage time. Storage containers should be inspected and reevaluated for the suitability of the storage location in regard to temperature fluctuations (temperature should be as stable as possible). Exposure to direct sunlight should be avoided.

PACKAGING

We supply this product in 25 litre cans and 200 litre drums. We can also ship in 1000 litre containers or in bulk.

Litres per piece	Packaging	Part no
25 litres	Can	11-1051-01
200 litres	Drum	11-1051-02
1000 litres	Container	11-1051-04
Bulk	Special request	

ENVIRO BY FOMTEC

The Fomtec Enviro range comprises an extensive range of non-PFAS based foams suitable for use Emergency Response missions and System applications. Enviro foam concentrates are available for class A, class B fire hazards and products are available for low, medium, and high expansion discharge devices.



enviro
by fomtec